Einstellwerte für gedrehte Kontakte
Settings for closed turned contacts

Werkzeuge / Tools
97 52 65 A / 97 52 65 DG A

Hinweis: Das Einstellmaß und die Locator-Position der Crimpzange sind entsprechend dem Leiterquerschnitt anzupassen.
Zur Ermittlung der hier aufgeführten Crimpeinstellungen wurde ein handelsübliches, feindrähtiges Litzenkabel verwendet. Die ermittelten Werte sind lediglich Richtgrößen und ohne Gewähr. Die Crimpeinstellungen sind vom Anwender mit der jeweils eingesetzten Litze konkret zu prüfen.

Note: The crimping depth and the locator position on the crimping tool must be adjusted to match the conductor cross-section.
A standard, fine-stranded cable was used to determine the crimping settings listed here. The values given are for guidance only and are provided without warranty.
The user must verify the crimping settings specifically for the stranded cable being used.

Hersteller Manufacturer	Locator Knipex	Nummer 1 Contact No. 1	Nummer 2 Contact No. 2	Steckerserie (Gehäuse) Connector series (housing)	Crimpkontaktserie Crimp contact series	Einstellmaß Setting dim. [mm]	Querschnitt Cross-section [mm²]	Locator- position
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	0,75	0,14	1
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	0,80	0,25	1
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	0,85	0,35	1
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	1,03	0,50	1
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	1,08	0,75	1
Hummel	97 59 65 HU1	7010941001		M23	Leistungskontakt	1,13	1,00	1
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	0,75	0,14	2
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	0,80	0,25	2
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	0,85	0,35	2
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	0,89	0,50	2
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	0,95	0,75	2
Hummel	97 59 65 HU1	7010941002		M23	Leistungssteckverbinder	1,02	1,00	2
Hummel	97 59 65 HU1	7010941021		M23	Leistungsverbinder	0,79	0,75	1
Hummel	97 59 65 HU1	7010941021		M23	Leistungsverbinder	0,86	1,00	1
Hummel	97 59 65 HU1	7010941021		M23	Leistungsverbinder	0,99	1,50	1
Hummel	97 59 65 HU1	7010941022		M23	Leistungssteckverbinder	0,79	0,75	2
Hummel	97 59 65 HU1	7010941022		M23	Leistungssteckverbinder	0,86	1,00	2
Hummel	97 59 65 HU1	7010941022		M23	Leistungssteckverbinder	0,99	1,50	2
Hummel	97 59 65 HU1	7010942001		M23	Leistungssteckverbinder	1,30	0,75	7
Hummel	97 59 65 HU1	7010942001		M23	Leistungssteckverbinder	1,40	1,00	7
Hummel	97 59 65 HU1	7010942001		M23	Leistungssteckverbinder	1,55	1,50	7
Hummel	97 59 65 HU1	7010942001		M23	Leistungssteckverbinder	1,70	2,50	7
Hummel	97 59 65 HU1	7010942002		M23	Leistungssteckverbinder	1,30	0,75	8
Hummel	97 59 65 HU1	7010942002		M23	Leistungssteckverbinder	1,40	1,00	8
Hummel	97 59 65 HU1	7010942002		M23	Leistungssteckverbinder	1,55	1,50	8
Hummel	97 59 65 HU1	7010942002		M23	Leistungssteckverbinder	1,70	2,50	8
Hummel	97 59 65 HU1	7010942011		M23	Leistungssteckverbinder	1,47	2,50	7
Hummel	97 59 65 HU1	7010942011		M23	Leistungssteckverbinder	1,60	4,00	7
Hummel	97 59 65 HU1	7010971001		M27	Signalverbinder	0,74	AWG 20	11
Hummel	97 59 65 HU1	7010971001		M27	Signalverbinder	0,72	AWG 22	11
Hummel	97 59 65 HU1	7010971001		M27	Signalverbinder	0,70	AWG 24	11
Hummel	97 59 65 HU1	7010971001		M27	Signalverbinder	0,68	AWG 26	11
Hummel	97 59 65 HU1	7010971002		M27	Signalverbinder	0,74	AWG 20	12
Hummel	97 59 65 HU1	7010971002		M27	Signalverbinder	0,72	AWG 22	12
Hummel	97 59 65 HU1	7010971002		M27	Signalverbinder	0,70	AWG 24	12
Hummel	97 59 65 HU1	7010971002		M27	Signalverbinder	0,68	AWG 26	12